# सहायक भीटाउ वाहन निरीसक परीसा-२००५

CODE: AYT 4. 72.79.04

प्रश्नपुस्तिका क्रमांक

100195

BOOKLET NO.

प्रश्नपुस्तिका

स्वयंचल अभियांत्रिकी

एकूण प्रश्न : 150


एकूण गुण : 300

सूचना

1) सदर प्रश्नपुस्तिकेत 150 अनिवार्य प्रश्न आहेत. उमेदवारांनी प्रश्नांची उत्तरे लिहिण्यास सुरुवात करण्यापूर्वी या प्रश्नपुस्तिकेत सर्व प्रश्न आहेत किंवा नाहीत याची खात्री करून घ्यावी. असा तसेच अन्य काही दोष आढळल्यास ही प्रश्नपुस्तिका समवेक्षकांकडून लगेच बदलन घ्यावी.

 आपला परीक्षा-क्रमांक ह्या चौकोनात न विसरता बॉलपेनने लिहावा.

वेळ : दीड तास



- 3) वर छापलेला प्रश्नपुस्तिका क्रमांक तुमच्या उत्तरपत्रिकेवर विशिष्ट जागी उत्तरपत्रिकेवरील सूचनेप्रमाणे **न विसरता नमूद करावा.**
- 4) (अ) या प्रश्नपुस्तिकेतील प्रत्येक प्रश्नाला 4 पर्यायी उत्तरे सुचिवली असून त्यांना 1, 2, 3 आणि 4 असे क्रमांक दिलेले आहेत. त्या चार उत्तरांपैकी सर्वात योग्य उत्तराचा क्रमांक उत्तरपत्रिकेवरील सूचनेप्रमाणे तुमच्या उत्तरपत्रिकेवर नमूद करावा. अशा प्रकारे उत्तरपत्रिकेवर उत्तरक्रमांक नमूद करताना तो संबंधित प्रश्नक्रमांकासमोर छायांकित करून दर्शविला जाईल याची काळजी घ्यावी, ह्याकरिता फक्त काळया शाईचे बॉलपेन वापरावे, पेन्सिल वा शाईचे पेन वापरू नथे.
  - (ब) आयोगाने ज्या विषयासाठी मराठी बरोबर इंग्रजी माध्यम विहित केलेले आहे. त्या विषयाचा प्रत्येक प्रश्न मराठी बरोबर इंग्रजी भाषेत देखील छापण्यात आला आहे. त्यामधील इंग्रजीतील किंवा मराठीतील प्रश्नामध्ये मुद्रणदोषांमुळे अथवा अन्य कारणांमुळे विसंगती निर्माण झाल्याची शंका आल्यास, उमेदवाराने संबंधित प्रश्न पर्यायी भाषेतील प्रश्नाशी ताडून पहावा.
- 5) सर्व प्रश्नांना समान गुण आहेत. यास्तव सर्व प्रश्नांची उत्तरे द्यावीत, घाईमुळे चुका होणार नाहीत याची दक्षता घेऊनच शक्य तितक्या वेगाने प्रश्न सोडवावेत. क्रमाने प्रश्न सोडविणे श्रेयस्कर आहे पण एखादा प्रश्न कठीण वाटल्यास त्यावर वेळ न घालिवता पुढील प्रश्नाकडे वळावे. अशा प्रकारे शेवटच्या प्रश्नापर्यंत पोहोचल्यानंतर वेळ शिल्लक राहिल्यास कठीण म्हणून वगळलेल्या प्रश्नांकडे परतणे सोईस्कर ठरेल.
- 6) उत्तरपत्रिकेत एकदा नमूद केलेले उत्तर खोडता येणार नाही. नमूद केलेले उत्तर खोडून नव्याने उत्तर दिल्यास ते तपासले जाणार नाही.
- 7) प्रस्तुत परीक्षेच्या उत्तरपत्रिकांचे मूल्यांकन करताना उमेदवाराच्या उत्तरपत्रिकेतील योग्य उत्तरांनाच गुण दिले जातील. त्या प्राप्त गुणांतून त्यांनी उत्तरपत्रिकेत चुकीची उत्तरे नमूद केल्याबद्दल गुण वजा केले जाणार नाहीत.

# ताकीद

ह्या प्रश्नपत्रिकेसाठी आयोगाने विहित केलेली वेळ संपेपर्यंत ही प्रश्नपुस्तिका आयोगाची मालमत्ता असून ती परीक्षाकक्षात उमेदवाराला परीक्षेसाठी वापरण्यास देण्यात येत आहे. ही वेळ संपेपर्यंत सदर प्रश्नपुस्तिकेची प्रत/प्रती, किंवा सदर प्रश्नपुस्तिकेतील काही आशय कोणत्याही स्वरूपात प्रत्यक्ष वा अप्रत्यक्षपणे कोणत्याही व्यक्तीस पुरविणे, तसेच प्रसिद्ध करणे हा गुन्हा असून अशी कृती करणाऱ्या व्यक्तीवर शासनाने जारी केलेल्या "परीक्षांमध्ये होणाऱ्या गैरप्रकारांना प्रतिबंध करण्याबाबतचा अधिनियम-82" यातील तरतुदीनुसार तसेच प्रचलित कायद्याच्या तरतुदीनुसार कारवाई करण्यात येईलव दोषी व्यक्ती कमाल एका वर्षाच्या कारावासाच्या आणि /िकंवा रुपये एक हजार रकमेच्या दंडाच्या शिक्षेस पात्र होईल.

तसेच ह्या प्रश्नपत्रिकेसाठी विहित केलेली वेळ संपण्याआधी ही प्रश्नपुस्तिका अनधिकृतपणे बाळगणे हा सुद्धा गुन्हा असून तसे करणारी व्यक्ती आयोगाच्या कर्मचारीवृंदापैकी, तसेच परीक्षेच्या पर्यवेक्षकीयवृंदापैकी असली तरीही अशा व्यक्तीविरूद्ध उक्त अधिनियमानुसार कारवाई करण्यात येईल व दोषी व्यक्ती शिक्षेस पात्र होईल.

8)

A W 77	-
A \/'	
A Y	

- 8) प्रश्नपुस्तिकेमध्ये विहित केलेल्या विशिष्ट जागीच कच्चे काम (रफ वर्क) करावे. प्रश्नपुस्तिकेव्यितिरिक्त-उत्तरपित्रकेवर वा इतर कागदावर कच्चे काम केल्यास ते कॉपी करण्याच्या उद्देशाने केले आहे, असे मानले जाईल व त्यानुसार उमेदवारावर शासनाने जारी केलेल्या "परीक्षांमध्ये होणाऱ्या गैरप्रकारांना प्रतिबंध करण्याबाबतचे अधिनियम-82" यातील तरतुदीनुसार कारवाई करण्यात येईल व दोषी व्यक्ती कमाल एका वर्षाच्या कारावासाच्या आणि / िकंवा रुपये एक हजार रकमेच्या दंडाच्या शिक्षेस पात्र होईल.
- 9) सदर प्रश्नपत्रिकेसाठी आयोगाने विहित केलेली वेळ संपल्यानंतर उमेदवाराला ही प्रश्नपुस्तिका स्वत:बरोबर परीक्षाकक्षाबाहेर घेऊन जाण्यास परवानगी आहे. मात्र परीक्षाकक्षाबाहेर जाण्यापूर्वी उमेदवाराने आपली उत्तरपत्रिका समवेक्षकाकडे न विसरता परत करणे आवश्यक आहे.

# नमुना प्रश्न

प्र.क. 201. Petrol Engine works on \_\_\_\_\_ cycle.

(1) Natural

(2) Air

(3) Otto

(4) Carnot

ह्या प्रश्नाचे योग्य उत्तर "(3) Otto" असे आहे. त्यामुळे या प्रश्नाचे उत्तर "(3)" होईल. यास्तव खालीलप्रमाणे प्र. क्र. 201 समोरील उत्तर क्रमांक "[3]" हा कंस पूर्णपणे छायांकित करुन दाखिवणे आवश्यक आहे.

प्र.क्र. 201. [1]

[2]

[4]

अशा पद्धतीने प्रस्तुत प्रश्नपुस्तिकेतील प्रत्येक प्रश्नाचा तुमचा उत्तरक्रमांक हा तुम्हाला स्वतंत्र्यरीत्या पुरविलेल्या उत्तरपत्रिकेवरील त्या त्या प्रश्नक्रमांकासमोरील संबंधित कंस पूर्णपणे छायांकित करुन दाखवावा. ह्याकरिता फक्त काळया शाईचे बॉलपेन वापरावे. पेन्सिल वा शाईचे पेन वापरू नये.

# पर्यवेक्षकांच्या सूचनेविना हे पृष्ठ उलटू नये

कच्च्या कामासाठी जागा Space For Rough Work

# **AUTOMOBILE ENGINEERING**

- 1. The property by which a body regains its original shape after removal of force is defined as
  - (1) plasticity

(2) elasticity

(3) ductility

- (4) malleability
- 2. Bending moment is maximum on a section of a beam where shear force is
  - (1) maximum

(2) minimum

(3) equal

- (4) changing sign
- 3. The ratio of change in volume and original volume of the body is called as
  - (1) tensile strain

(2) compressive strain

(3) shear strain

- (4) volumetric strain
- 4. A shaft of diameter (d) subject to a bending moment (M) and a twisting moment (T) at a section. The maximum shear stress is given by the equation
  - (1)  $\tau_{\text{max}} = \frac{16}{\pi d^3} \sqrt{M^2 + T^2}$
- (2)  $\tau_{\text{max}} = \frac{16}{d^3} \sqrt{M^2 + T^2}$

(3)  $\tau_{\text{max}} = \frac{16}{\pi \text{ d}^3} \sqrt{1 + \text{T}^2}$ 

(4)  $\tau_{\text{max}} = \frac{16}{\pi d^3} \sqrt{M^2 + 1}$ 

- 5. In case of column
  - (1) one end is hinged and other end fixed
  - (2) one end is fixed and other end free
  - (3) both ends are hinged
  - (4) both the ends are fixed rigidly
- 6. Slenderness ratio of a column may be defined as the ratio of its length to the
  - (1) radius of column
  - (2) minimum radius of gyration
  - (3) maximum radius of gyration
  - (4) none of the above

- 7. What will be the thickness of metal required for a cast iron main 800 mm in diameter for water at a pressure head of 100 m if the maximum permissible tensile stress is 20 MN/m<sup>2</sup> and weight of water is 10 kN/m<sup>3</sup>.
  - (1) 15 mm

(2) 20 mm

(3) 25 mm

- (4) 30 mm
- 8. In case of circular section, the section modulus is given by
  - (1)  $\frac{\pi d^2}{16}$

(2)  $\frac{\pi d^3}{16}$ 

(3)  $\frac{\pi d^3}{32}$ 

- (4)  $\frac{\pi d^4}{64}$
- 9. If the two axes about which the product of inertia is found, are such that the product of inertia becomes zero, the two axes are called as
  - (1) centroidal axes
  - (2) principal axes
  - (3) major and minor axes
  - (4) none of the above
- 10. Which one of the basic equation of simple bending is correct

where I = Moment of Inertia

E = Modulus of Elasticity

F = Stress at any fibre at a distance of y from neutral axis

M = Bending moment

R = Radius of curvature

 $(1) \quad \frac{M}{I} = \frac{F}{Y} = \frac{E}{R}$ 

 $(2) \quad \frac{M}{I} = \frac{F}{Y} = \frac{R}{E}$ 

 $(3) \quad \frac{F}{I} = \frac{M}{Y} = \frac{E}{R}$ 

 $(4) \quad \frac{F}{I} = \frac{Y}{M} = \frac{R}{E}$ 

#### AYT



11. The shear angle for two dimensional cutting operation is given by an equation

where r = cutting ratio

 $\alpha$  = rake angle

 $\phi$  = shear angle

(1)  $\tan \phi = \frac{r \cos \alpha}{1 + r \sin \alpha}$ 

(2)  $\tan \phi = \frac{r \cos \alpha}{1 - r \sin \alpha}$ 

(3)  $\tan \phi = \frac{1 - r \sin \alpha}{r \cos \alpha}$ 

(4)  $\tan \phi = \frac{1 + r \sin \alpha}{r \cos \alpha}$ 

12. The standard point angle of drill used for drilling a wood and fibre is

(1) 116° to 118°

(2) 130° to 140°

(3) 60°

(4) 125°

13. Which one of the following process is preferred for improving the surface finish of a job?

(1) Milling

(2) Turning

(3) Super finishing

(4) Drilling

14. Which one of the following is a type of brass?

(1) Babbit metal

(2) Gun metal

(3) Monel metal

(4) Muntz metal

15. In which process the principle of electrolysis is used to remove metal from workpiece?

- (1) EDM (Electrodischarge Machining)
- (2) ECM (Electrochemical Machining)
- (3) EDG (Electrodischarge Grinding)
- (4) USM (Ultrasonic Machining)

16. Hot short phenomenon occurs in steel because of excess amount of

(1) manganese

(2) sulphur

(3) silicon

(4) phosphorus

				AYT
17.		holding irregular shaped work and able.	carrying	g out eccentric turning is most
	(1)	four jaw chuck	(2)	three jaw chuck
	(3)	collet chuck	(4)	face plate
18.		ognize the type of defect in casting ing with respect to each other.	caused	due to shift of the individual parts of a
	(1)	Blow holes	(2)	Mismatch
	(3)	Swell	(4)	Warpage
19.	Exti	rusion is a type of operation.		
	(1)	Hot Working and Cold Working	(2)	Welding
	(3)	Casting	(4)	Fitting
20.	For	holding work piece, which is already of	drilled o	or bored, is used on lathe.
	(1)	collet chuck	(2)	face plate
	(3)	angle plate	(4)	mandrel
21.	In la	athe, tumbler gear mechanism is used t	o contr	ol motion of
	(1)	tool carriage	(2)	job
	(3)	tool post	(4)	tail stock
22.		ich type of thread is generally used	d for s	plit nut of lead screw of screw cutting
	(1)	Square	(2)	Vee
	(3)	Butress	(4)	ACME
23.	A pl	laner differs from shaper in one import	ant asp	ect that, in planer,
	(1)	the work is fixed while tool reciproca		
	(2)	the work reciprocates while tool is fi	xed	
	(3)	the work and tool, both move		
	(4)	the work and tool, both do not move		

AY]	Γ			Ö							
24.		process of removing metal by an elon easing size, which cut in a fixed path i		tool having a number of successive teeth of vn as,							
	(1)	reaming	(2)	boaring							
	(3)	broaching	(4)	honing							
25.		property by virtue of which sand mou molten metal without fusing is known		apable of withstanding high temperature of							
	(1)	porosity	(2)	adhesiveness							
	(3)	cohesiveness	(4)	refractoriness							
26.		threading is generally used for gas, water or steam pipe joints.									
	(1)	BSW	(2)	BSE							
	(3)	BSP	(4)	None of these							
27.	Тоо	l Steel (HSS) has following elements.									
	(1)	Tungsten, Chromium, Vanadium									
	(2)	Chromium – Nickel									
	(3)	Tungsten, Chromium, Lead									
	(4)	None of these									
28.	For	marking round shaped work piece	can	be used.							
	(1)	Vee block	(2)	Angle plate							
	(3)	Try square	(4)	None of these							
29.		are used for withdrawing pattern from	m the	mould.							
	(1)	Riddles	(2)	Draw spikes							
	(3)	Vent wire	(4)	Slicks							
30.	Incl	uded angle of the centre for heavy worl	k in lat	he is							
	(1)	45°	(2)	60°							
	(3)	75°	(4)	none of these							

P.T.O.

31.	Whi	ch one of the following is the best	example o	of higher Kinematic Pair?					
	(1)	Universal joint	(2)	Shaft rotating in a bearing					
	(3)	Nut turning on a screw	(4)	Cam and follower					
32.		ch one of the following relationshifticient of friction (µ)?	nip holds	good to express angle of friction (φ) and					
	(1)	$\tan \phi = \mu$	(2)	$\sin \phi = \mu$					
	(3)	$\cos \phi = \mu$	(4)	$\cot \phi = \mu$					
33.	The	ratio of pitch diameter to the numb	er of teeth	, in a gear drive is termed as					
	(1)	circular pitch	(2)	gear ratio					
	(3)	module	(4)	none of the above					
	leve (1)								
	(2)	No							
	(3)	Insufficient data to predict the rest	ult						
	(4)	None of the above							
35.	Asso	ertion (A): Spiral cams find its use	e in comp	uters.					
	Rea	son (R): Spiral cams have two t	ypes of su	urfaces, convex and concave.					
	(1)	(1) Both (A) and (R) are true and (R) is the correct explanation for A							
	(2) (A) is true and (R) is not the correct reason for (A)								
	(3) (A) is false and (R) is true								
	(4)	Both (A) and (R) are false statement	ents						
36.		Which one of the follower is widely used and has a cylindrical roller free to rotate about pin joint?							
	(1)	Knife-edge follower	(2)	Roller follower					
	(3)	Mushroom follower	(4)	All the above					

AYT	•									
<b>37.</b>	Whi	ich of the following circle is in	naginary circle	in study of gears?						
	(1)	Pitch circle	(2)	Addendum circle						
	(3)	Dedendum circle	(4)	All of them						
38.	- Whi	ich of the following statement	is correct ?							
	(1)	The force of friction does no	t depend upon	area of contact of two surfaces						
	(2)	The magnitude of limiting between two surfaces	friction bears	a constant ratio to the normal rea	action					
	(3)	The force of friction depend	upon area of co	ontact of two surfaces						
	(4)	Both (1) and (2)								
39.	Dynamically unbalanced masses in rotating machines cause									
	(1)	vibration	(2)	noise						
	(3)	friction	(4)	wear						
40.	In a plate cam mechanism, with reciprocating roller follower, the follower has consacceleration in case of									
	(1)	cycloidal motion	(2)	S.H.M.						
	(3)	parabolic motion	(4)	none of the above						
41.	A co	onstant discharge passing throu	igh a conical pi	ipe is an example of						
	(1)	steady uniform flow								
	(2)	steady non-uniform flow								
	(3)	unsteady uniform flow								
	(4)	unsteady non-uniform flow								
42.	Visc	cosity has the dimensions								

(2)  $FL^{-1}T^{-1}$ 

(4) FL<sup>2</sup> T

where F is force, L is length and T is time

(1)  $FL^{-2}T$ 

(3) FLT<sup>-2</sup>

43.	The	centre of	buoya	incy of	f a su	bmerged	body

- (1) coincides with the centre of gravity of the body.
- (2) is always below the centre of gravity of the body.
- (3) coincides with the centroid of the displaced volume of the fluid.
- (4) is always above the centroid of the displaced volume of the fluid.

# 44. The type of pump similar to propeller turbine is

(1) lobe pump

(2) jet pump

(3) injector pump

(4) axial flow pump

#### **45.** An impulse turbine

- (1) requires draft tube
- (2) is most suited for low head application
- (3) operates by initial complete conversion to kinetic energy
- (4) is not exposed to atmosphere

### **46.** Hydraulic intensifier is a device used for

- (1) storing energy of fluid in the form of pressure energy
- (2) increasing pressure intensity of fluid
- (3) transmitting power from one shaft to other
- (4) none of the above

# 47. Hydraulic Ram is a pump which works on

- (1) the principle of water hammer
- (2) the principle of reciprocating action
- (3) the principle of centrifugal action
- (4) none of the above

AYT	Γ										
48.	Prin	ciple of Hydraulic accumulator is	s similar to t	he principle of							
	(1)	electrical transformer	(2)	electrical battery							
	(3)	electrical generator	(4)	electrical motor							
49. 50. 51.	cons	A vertical circular cylinder is filled with water and then rotated about its vertical axis at a constant speed such that half the liquid spills out from the open top. At that instant, pressur at the centre of bottom should be									
	(1)	atmospheric pressure									
	(2)	sub-atmospheric pressure									
	(3)	one fourth of original value									
	(4)	more than atmospheric pressure	;								
50.	The fluids which have linear relationship between the magnitude of shear stress and the resulting rate of deformation are called										
	(1)	Ideal fluids		•							
	(2)	Non- Newtonian fluids									
	(3)	Newtonian fluids									
	(4)	Compressible fluids									
51.	Whi	ich of the following does not rela	te to a spark	ignition engine ?							
	(1)	Ignition coil	(2)	Spark plug							
	(3)	Distributor	(4)	Fuel injector							
52.	The	ideal cycle on which steam engir	ne works is								
	(1)	Carnot cycle	(2)	Rankine cycle							
	(3)	Otto cycle	(4)	Joule cycle							
53.	The	isentropic process on Mollier dia	igram is repr	resented by							
	(1)	horizontal line	(2)	vertical line							
	(3)	inclined line	(4)	curved line							

į

**54.** The dryness fraction of steam is equal to \_\_\_\_\_

where  $m_g$  is mass of dry steam and  $m_f$  mass of water in suspension.

(1)  $m_g / (m_g + m_f)$ 

(2)  $m_f / (m_g + m_f)$ 

(3)  $m_g/m_f$ 

- (4)  $m_f/m_g$
- 55. The locus of saturated liquid line and saturated vapour line meets at
  - (1) boiling point

(2) ice point

(3) triple point

- (4) critical point
- **56.** The effect of under cooling the refrigerant is to
  - (1) reduce the refrigerating effect
  - (2) increase the super heat of vapour
  - (3) reduce the C.O.P. of the cycle
  - (4) increase the C.O.P. of the cycle
- **57.** Which one of the following conditions is the most suitable condition for comfort air conditioning?
  - (1) 25 °C DBT and 100% R.H.
  - (2) 20 °C DBT and 80% R.H.
  - (3) 22 °C DBT and 60% R.H.
  - (4) 28 °C DBT and 40% R.H.
- **58.** Which chemical is liberated during geothermal power generation?
  - (1) Sulphur

(2) Oxygen

(3) Carbondioxide

(4) Nitrogen

		_
A	v	Г
_		

59. Assertion (A): Steam expands in nozzles of impulse steam turbine.

**Reason (R):** Pressure of steam is converted into kinetic energy of steam in the nozzles.

- (1) Both (A) and (R) are true
- (2) Only (A) is true
- (3) Only (R) is true
- (4) Both (A) and (R) are not true
- **60.** During cut-off governing of a steam engine, which one of the following parameter changes?
  - (1) Speed
  - (2) Steam pressure
  - (3) Volume of steam supplied per stroke
  - (4) Pressure and volume of steam supplied
- 61. Which calorific value of a fuel should be considered for calculation of thermal efficiency of a power plant?
  - (1) Lower calorific value
  - (2) Higher calorific value
  - (3) Gross heating value
  - (4) None of the above
- 62. A refrigerant machine working on reversed Carnot cycle consumes 3 kW for producing refrigerating effect of 500 kJ/min, for maintaining region at 40 °C, the higher temperature of the cycle will be

15

(1) 317 K

(2) 44 K

(3) 44 °C

(4) 233 K

- **63.** Consider the following statements
  - (A): Efforts are made to harness non conventional energy sources for power generation.
  - (R) : The conventional energy sources will be exhausted soon.

Now select the answer from the following alternatives.

- (1) Both (A) and (R) are true, but (R) is not the correct reason for (A)
- (2) (A) is true, but (R) is false
- (3) (R) is true, but (A) is false
- (4) Both (A) and (R) are true and (R) is the correct reason for (A)
- **64.** Match List-I with List-II using the correct code given below :

						8
			Lis	st-I		List-II
	A	So	lar Er	nergy	I	Ocean waves
	В	Ti	dal Er	nergy	$\Pi$	Steam from earth
	C	Ge	eother	mal Energy	III	Atomic fission
	D	Go	bar g	as plant	ſV	Flat plate collector
					V	Anaerobic digestion
	A	В	C	D		
(1)	I	II	Ш	IV		
(2)	П	Ш	ſV	V		
(3)	IV	I	II	V		
(4)	V	I	II	III		

- **65.** Assertion (A): The volumetric efficiency of Reciprocating Compressor (with clearance) is always less than 100%.
  - **Reason (R):** The air present in the clearance volume will expand before the intake conditions are reached and it occupies some volume of cylinder.
  - (1) Both (A) and (R) are true and (R) is not the correct explanation for (A)
  - (2) Both (A) and (R) are true and (R) is true reason for (A)
  - (3) (A) is true, but (R) is false
  - (4) Both (A) and (R) are false

where Polytropic law  $PV^n = c$ 

 $U_a = Effective swept volume$ 

 $P_1$  = Suction pressure

 $P_2$  = Final compressor pressure

(1) 
$$W = \frac{n}{n-1} \frac{P_1}{U_a} \left\{ \left( \frac{P_2}{P_1} \right)^{\frac{n-1}{n}} - 1 \right\}$$

(2) 
$$W = \frac{n-1}{n} P_1 U_a \left\{ \left( \frac{P_2}{P_1} \right)^{\frac{n-1}{n}} - 1 \right\}$$

(3) 
$$W = \frac{n}{n-1} P_1 U_a \left\{ \left( \frac{P_2}{P_1} \right)^{\frac{n-1}{n}} - 1 \right\}$$

(4) 
$$W = \frac{n}{n-1} P_1 U_a \left\{ \left( \frac{P_1}{P_2} \right)^{\frac{n-1}{n}} - 1 \right\}$$

- 67. Isothermal compression for high speed compressor is achieved by the method
  - (1) water jacketing

(2) inter-cooling

(3) external fins

- (4) all the above
- 68. Which one of the following air compressors is generally used in the gas turbines?
  - (1) Axial flow rotary compressors
  - (2) Radial blowers
  - (3) Sliding vane compressors
  - (4) Screw compressors
- **69.** The efficiency of vane type air compressor as compared to roots air compressor for the same pressure ratio is \_\_\_\_\_\_.
  - (1) more

(2) less

(3) same

(4) may be more or less

- 70. In Reciprocating air compressor the method of controlling the quantity of air delivered is done by
  - (1) throttle control

(2) blow-off control

(3) clearance control

- (4) all the above
- 71. The work input to air compressor is minimum if the compression law followed is \_\_\_\_\_
  - (1)  $PV^{1.35} = C$

(2) Isothermal PV = C

(3) Isentropic PV  $^{r} = C$ 

- (4)  $PV^{1.2} = C$
- 72. In centrifugal air compressor the pressure developed depends on
  - (1) impeller tip velocity

(2) inlet temperature

(3) compression Index

- (4) all the above
- 73. The clearance volume in Reciprocating air compressor is provided to
  - (1) reduce the work done / kg of air delivered
  - (2) increase the volumetric efficiency of compressor
  - (3) accommodate valves in the head of the compressor
  - (4) create turbulence in the air to be delivered
- **74.** What should be the intermediate pressure in two stage compression for minimum work of compression?

 $P_a = Suction pressure$ 

P<sub>i</sub> = Intermediate pressure

 $P_d$  = Delivery pressure

 $(1) \quad P_i = \sqrt{P_a P_d}$ 

 $(2) P_i = \frac{P_d}{P_a}$ 

 $(3) \quad P_i = P_a \times P_d$ 

 $(4) P_i = \sqrt{\frac{P_o}{P_a}}$ 

AYT	1								
75.			the folessor?		ng effic	iency is	high	ly sensi	tive to a clearance volume of reciprocating
	(1)	Mec	hanica	l effi	ciency			(2)	Isothermal efficiency
	(3)	Adia	abatic o	effici	ency			(4)	Volumetric efficiency
76.	If th	e dom	nestic r	efrig	erator is	kept in	an ir	sulated	room, with its door open
	(1)	the t	emper	ature	of the r	oom sh	all de	crease a	after sometime
	(2)	the t	emper	ature	of the r	oom sh	all in	crease a	fter sometime
	(3)	the t	emper	ature	of the r	oom sh	all re	main un	affected
	(4)	noth	ing ca	n be	predicte	d about	the to	emperat	ure of the room
77.	Air	refrige	eration	syste	em oper	ates on		_	
	(1)	reve	rsed C	arno	cycle			(2)	reversed Brayton cycle
	(3)	reve	rsed O	tto c	ycle			(4)	reversed Stirling cycle
78.					ergy car ther is k			created	nor be destroyed but can only be converted
	(1)	Avo	gadro'	s hyp	oothesis			(2)	Gay-Lussac's law
	(3)	Seco	ond La	w of	thermod	lynamic	cs	(4)	First Law of thermodynamics
79.	Mat	ch Lis	st-I wit	h Lis	t-II and	select t	he co	rrect co	de.
			List	t-I				List-I	Į.
		A	Hea	vy w	ater		I	Diesel	Engine
		В	Ran	kine	cycle		П	Gas Tr	urbine
		C	Fue	l pun	np		Ш	Therm	al Power Plant
		D	Air	com	pressor		ſV	Nuclea	ar Reactor
		Α	В	C	D				

(1) III I

(4) IV III

(2) II

(3) I

II

Ш

II

I

IV

Ш

ΙV

I

IV

II

- 80. Select a false statement for Spark Ignition (SI) engine.
  - (1) It is based on Otto cycle
  - (2) Requires an ignition system with spark plug in the combustion chamber
  - (3) Compression ratio = 6 to 10.5
  - (4) Low self ignition temperature of fuel is desirable
- 81. The thermal efficiency of the ideal diesel cycle is given by equation

where  $\rho$  = Cut off ratio

R = Compression ratio

- $(1) \quad \eta = 1 \frac{1}{R^{r-1}} \left( \frac{\rho^r 1}{r \left( \rho 1 \right)} \right)$
- (2)  $\eta = 1 \frac{1}{R^{r-1}}$
- (3)  $\eta = 1 \frac{1}{R^{r-1}} \left( \frac{r(\rho 1)}{\rho^r 1} \right)$
- (4) none of the above
- 82. In an ideal Otto cycle the air standard efficiency is 56.5%. If the heat added during the constant volume process is 1000 kJ/kg, determine the work done.
  - (1) 1000 kJ/kg

(2) 1500 kJ/kg

(3) 565 kJ/kg

- (4) None of the above
- 83. The duration of the ignition lag in an engine depends on the factors like
  - (1) chemical nature of fuel
- (2) mixture ratio

(3) electrode gap

- (4) all the above
- 84. Select the most appropriate sentence applicable to knocking phenomena of the S.I. engine
  - (1) In S.I. engine, the detonation occurs near the end of combustion.
  - (2) In S.I. engine, the detonation occurs near the beginning of combustion.
  - (3) In S.I. engine, the detonation is of a heterogeneous mixture causing very low rate of pressure rise.
  - (4) None of the above

<b>AYT</b>				
35.			el and i	mixes it with air, and is the most importan
	•	of the induction system in an engine.	(2)	Followski manifold
	(1)	Spark plug	(2)	Exhaust manifold
	(3)	Carburettor	(4)	Silencer
86.	Whi	ich one of the following device is need	led for	carburettor used in aircraft application?
	(1)	Altitude mixture correction device		
	(2)	Automatic de-icing unit to avoid for	mation	of ice in the choke tube
	(3)	Both (1) and (2)		
	(4)	None of the above		
<b>37.</b>	for o	•	consun	nation of engine friction is only applicable option is plotted against brake power and it?
	(1)	Morse test	(2)	Motoring method
	(3)	Deceleration method	(4)	William's line method
88.	In a	diesel engine		
	(a)	fuel injection pump is used		
	(b)	fuel injection pump and carburettor i	s used	
	(c)	fuel injector is used		
	(d)	neither fuel injection pump nor injec	tor is u	sed
	(1)	(a) alone is true	(2)	(c) alone is true
	(3)	(a) and (c) both are true	(4)	(a), (b), (c), (d), all are true
89.		cooling is a process of cooling the	e refrig	gerant at constant pressure, in a vapour
	(1)	after compression	(2)	before throttling
	(3)	before compression	(4)	after evaporation
90.	Whi	ich of the following is a fossil fuel?		
	(1)	Coal	(2)	Wood
	(3)	Natural Uranium	(4)	Hydrogen
	- /		, ,	-

					AYT					
<u>9</u> 1.	The	two stroke cycle engine has port in the			7.1.1					
, <b>.</b> .	(1)	cylinder walls	(2)	pistons						
	(3)	piston rings	(4)	cylinder head						
92.	In a	diesel engine fuel and air mixture is ig	nited b	by the help of						
	(1)	a spark plug	(2)	a glow plug						
	(3)	an injector	(4)	temperature of compressed air						
93.	On	many engines, the valve timing can be	checke	ed by means of marking on the	•					
	(1)	engine fly wheel	(2)	valve guide						
	(3)	vibration damper	(4)	valve cover						
94.	The	The purpose of chilled passage in the crank shafts is to								
	(1)	) lubricate the main bearings								
	(2)	lubricate the connecting rod bearings								
	(3)	reduce the manufacturing cost								
	(4)	none of the above								
95.	Mul	tiple jet compensation is a provision fo	r							
	(1)	(1) overcoming difficulties at different speeds in petrol engines								
	(2)	(2) multipoint fuel injection in petrol engines								
	(3)	3) advanced electronic fuel injection system on petrol engines								
	(4)	efficient operation of super chargers a	at high	altitude						
96.	The	contact breaker points gap can be adju-	sted by	· · · · · · · · · · · · · · · · · · ·						
	(1)	stroboscope	(2)	tachometer						
	(3)	ignition tester	(4)	feeler gauge						

(2) nichrome

(4) white metal

97. The radiator core is generally made up of

stainless steel

brass

(1)

(3)

AYI								
98.	Cyli	inder wear is measured with						
	(1)	vernier	(2)	micrometer				
	(3)	dial gauge	(4)	bore dial gauge				
99.	Dur	ing the power stroke in a four stroke	engine, t	he inlet valve and exhaust valves are				
	(1)	closed and opened respectively						
	(2)	both closed						
	(3)	opened and closed respectively						
	(4)	one open and other closed						
100.	The	The part that tends to keep the valve closed is called the						
	(1)	valve guide	(2)	valve retainer				
	(3)	valve spring	(4)	valve lifter				
101.		The pump part that rotates and causes water circulation between the radiator and the engine is called the						
	(1)	fan	(2)	by-pass				
	(3)	thermostat	(4)	impeller				
102.		During high speed operation when the throttle is wide open, the fuel supplied to the engine is discharged through the						
	(1)	low-speed port						
	(2)	idle port						
	(3)	main nozzle						
	(4)	both low speed and idle port						
103.	The	pressure in the vicinity of main jet of	a carbu	rettor remains				
	(1)	above atmospheric pressure						
	(2)	equal to atmospheric pressure		•				
	(3)	much below atmospheric pressure						
	(4)	very high pressure						

			AY	T				
The	amount of heat energy equivalent le	ost in over	rcoming engine friction is					
(1)	30%	(2)	20%					
(3)	15%	(4)	5%					
The	rmal efficiency of a two stroke cycl	e engine is	s a four stroke cycle engine					
(1)	less than	(2)	greater than					
(3)	equal to	(4)	greater than or equal to					
The firing order of an I.C. engine depends upon								
(1)	design of crankshaft	(2)	no. of cylinders					
(3)	arrangement of cylinders	(4)	all of the above					
Thro	ottle valve is used in carburettor for							
(1)	1) controlling the air admitted to venturi							
(2)	(2) controlling the air admitted and oil admitted to engine							
(3)	(3) controlling the air-petrol mixture admitted to engine							
(4)	(4) controlling the mixture of air and fuel in the mixing chamber							
Commonly used antifreeze solution in automobiles is								
(1)	Glycerine	(2)	Liquid ammonia					
(3)	Ammonium chloride	(4)	Carbon disulphide					
Wha	at is Vapour Lock ?			_				
(1)		of petrol di	ue to vapour formation at higher temp.					
		•						
. ,	-	-						
. ,	·							
	(1) (3) The (1) (3) The (1) (3) Thre (1) (2) (3) (4)  Con (1) (3) What	(1) 30% (3) 15%  Thermal efficiency of a two stroke cycle (1) less than (3) equal to  The firing order of an I.C. engine deper (1) design of crankshaft (3) arrangement of cylinders  Throttle valve is used in carburettor for (1) controlling the air admitted to ver (2) controlling the air admitted and o (3) controlling the air-petrol mixture (4) controlling the mixture of air and  Commonly used antifreeze solution in a (1) Glycerine (3) Ammonium chloride  What is Vapour Lock? (1) Phenomenon of irregular supply of (2) Phenomenon of cut off diesel sup (3) Phenomenon of overflow of petro	(1) 30% (2) (3) 15% (4)  Thermal efficiency of a two stroke cycle engine is (1) less than (2) (3) equal to (4)  The firing order of an I.C. engine depends upon (1) design of crankshaft (2) (3) arrangement of cylinders (4)  Throttle valve is used in carburettor for (1) controlling the air admitted to venturi (2) controlling the air admitted and oil admitted (3) controlling the mixture of air and fuel in the controlling the mixture of air and fuel in the Commonly used antifreeze solution in automobile (1) Glycerine (2) (3) Ammonium chloride (4)  What is Vapour Lock? (1) Phenomenon of irregular supply of petrol decay (2) (2) Phenomenon of overflow of petrol	The amount of heat energy equivalent lost in overcoming engine friction is  (1) 30% (2) 20%  (3) 15% (4) 5%  Thermal efficiency of a two stroke cycle engine is a four stroke cycle engine  (1) less than (2) greater than  (3) equal to (4) greater than or equal to  The firing order of an LC. engine depends upon  (1) design of crankshaft (2) no. of cylinders  (3) arrangement of cylinders (4) all of the above  Throttle valve is used in carburettor for  (1) controlling the air admitted to venturi  (2) controlling the air admitted and oil admitted to engine  (3) controlling the mixture of air and fuel in the mixing chamber  Commonly used antifreeze solution in automobiles is  (1) Glycerine (2) Liquid ammonia  (3) Ammonium chloride (4) Carbon disulphide  What is Vapour Lock?  (1) Phenomenon of cut off diesel supply  (3) Phenomenon of overflow of petrol				

AYT				
110.	Eng	ine cranks do no start during winter	r because o	of
	(a)	battery discharge	(b)	weak spark
	(c)	worn out engine	(d)	lean mixture
	(1)	(a), (b) and (c) are correct	(2)	(b), (c) and (d) are correct
	(3)	(c), (d) and (A) are correct	(4)	(d), (a) and (b) are correct
111.		en the rear wheels are jacked up ar drive in anticlockwise direction, w		re in neutral, turning one rear wheel of the ne other to
	(1)	turn in clockwise direction	(2)	turn in anticlockwise direction
	(3)	turn in either direction	(4)	remain stationary
112.	Toro	que converter can replace		
	(a)	gear box		
	(b)	clutch		
	(c)	fluid fly wheel		
	(1)	(a) alone is correct	(2)	(b) alone is correct
	(3)	(c) alone is correct	(4)	(a) and (b) are correct
113.	Flyv	wheels are used in		
	(a)	bicycles		
	(b)	starting motor		
	(c)	gear boxes		
	(1)	(a) alone is correct	(2)	(c) alone is correct
	(3)	(a) and (c) are correct	(4)	all are correct
114.	Inde	ependent suspension on all four whe	els is used	l in
	(1)	Maruti 800 car	(2)	A.C. sports car
	(3)	Morgon plus 8 car	(4)	Fiat 1100 car
115.	The	brake pipes in hydraulic brake syst	em are ma	de of
	(1)	rubber	(2)	steel
	(3)	nyc	(4)	aluminium

ب									AII		
116.	Traf	Trafficators are lights used for									
	(1) heavy traffic										
	(2)	light traffic									
	(3) reversing the car in traffic										
	(4)	indi	cating	g the	direction	in which it t	urns				
117.	Aluı	miniu	m cyl	inder	blocks re	equires			_		
	(1)	no li	iners				(2)	aluminium liners			
	(3)	bras	s line	ers			(4)	cast iron liners			
118.	The	value	s of v	wheel	lock ang	le and the st	eering l	ock angle respectively are abo	out		
	(1)	46°	and 4	3°			(2)	20° and 23°			
	(3)	23°	and 2	20°			(4)	43° and 46°			
119.	Which of the following is correct statement?										
	(1) The car bonnet should have a longer length										
	(2) The texture of a hard top roof is different from its body work										
	(3)	(3) Side impact can be minimized by 2 + 2 seating layout									
	(4)	A re	clinii	ng sea	at and sid	e shift aisle :	seat are	almost the same			
120.	Mat lists		st-I v	vith I	List-II and	d choose the	e correc	t answer from the codes give	en below the		
				Li	st-I		L	ist-II			
		A.	Ta	chon	neter	1.	Bimet	al electric type			
		B.	O	dome	ter	2.	Decib	el			
		C.	Fu	iel ga	uge	3.	90 km	ph			
		D.	Pr	essur	e horn	4.	6000 r	pm			
						5.	37501	xm			
	Cod	Code:									
		A	В	C	D						
	(1)	4	5	1	2						
	(2)	5	4	2	1						
	(3)	3	4	2	1	,					
	(4)	4	2	1	3						

AYT	,							
121.	The	spark plug generally is to be re	eplaced when t	the vehicle has run about				
	(1)	5000 km	(2)	10000 km				
	(3)	15000 km	(4)	20000 km				
122.	The	recommended oil change sched	dule for cars is					
	(1)	15000 km	(2)	one year duration				
	(3)	9 months duration	(4)	10000 km				
	[No	[Note: Assume in each option other recommended schedule has not yet attained.]						
123.	The number of points at which the engine-clutch-gear box unit is supported on the chass frame is							
	(1)	one	(2)	two				
	(3)	three	(4)	four				
124.	The most effective section of frame against bending is							
	(1)	rectangular bar section						
	(2)	round bar section						
	(3)	(3) round hollow section						
	(4)	square hollow section						
125.	Wh	y bendix drive is provided for a	starter?					
	(1)	To restart the drive pinion fro	m flywheel af	ter the engine starts				

126. The type of commercial vehicle which connects tractor to the trailer by a fifth wheel

(2)  $8 \times 5$ 

articulated

(4)

(2)

(3)

(4)

To start the motor

To drive flywheel

coupling is called

(1)  $6 \times 5$ 

(3) rigid

To operate solenoid

14/.	A CI	A clutch is usually designed to transmit maximum torque which is								
	(1)	equal to the maximum engine	torque							
	(2)	80 percent of the maximum to	orque							
	(3)	150 percent of the maximum t	torque							
	(4)	none of the above								
128.	The	oil flow in the torus of a torque	converter is	of						
	(1)	(1) spiral and vortex type								
	(2)	steady, uniform and laminar ty	ypes							
	(3)	vortex, rotary and spiral types								
	(4)	none of the above								
129.	Coefficient of friction between the correctly inflated tyre of a jeep and the icy surface Srinagar in Jammu and Kashmir is about									
	(1)	0.01	(2)	0.55						
	(3)	111.3	(4)	0.10						
130.		For the best braking performance the braking effort on the front wheels and the rear wheels are in the following proportion:								
	(1)	50%; 50%	(2)	40%; 60%						
	(3)	60%; 40%	(4)	45%; 55%						
131.	Cap	Capacity of storage battery to convert chemical energy into electrical energy is tested by								
	(1)	hydrometer test	(2)	high discharge test						
	(3)	specific gravity test	(4)	arc test						
132.	Eng	Engine emits white smoke due to								
	(1)	excessive lean mixture								
	(2)	excessive rich mixture								
	(3)	excessive oil with fuel								
	(4)	worn out piston rings								
	_									

A	v	т
А	1	1

ı	ŕ	-	ิ	
ı	Ļ	-	J	

133.	Car	pulls to one side while braking due t	o						
	(1)	frame misaligned	(2)	loose rear springs					
	(3)	unequal load in car	(4)	brake grabs					
134.	Dur	ing battery charge, the electrolyte bec	comes						
	(1)	colder	(2)	thinner					
	(3)	lighter	(4)	heavier					
134. 135. 136.	Exhaust valve temperature is about								
	(1)	35 °C	(2)	100 °C					
	(3)	500 °C	(4)	1000 °C					
136.	Humming noise in the differential is due to improper tooth contact between								
	(1)	drive pinion and ring gear							
	(2)	•							
	(3)	pinion and gears							
	(4)	shafts and bearings							
136.	Whi	ich type of rear axle is generally used	in heav	y commercial vehicles ?					
	(1)	Semi floating axle							
	(2)	Fully floating axle							
	(3)	Three quarter floating axle							
	(4)	Plain axle							
138.	An	instrument called hydrometer is used	for						
134. 135. 136.	(1)	measuring specific gravity of acid							
	(2)	measuring viscosity of an oil							
	(3)	measuring temp of water							
	(4)	measuring charging of battery							

_						
139.	The	probable cause for hard steering	could be			
	(1)	low tyre pressure	(2)	bent wheel spindle		
	(3)	tie rod end tight	(4)	any of the above		
140.	The	tightening torque required for cyl	linder head l	bolts in motor cycles generally lie between		
	(1)	5 to 10 N-m	(2)	10 to 20 N-m		
	(3)	25 to 30 N-m	(4)	40 to 60 N-m		
141.	Mos	st of the mopeds in India have cap	acity of			
	(1)	100 CC	(2)	50 CC		
	(3)	150 CC	(4)	120 CC		
142.	In w	which of the following documents,	, the details	of the vehicle tax are recorded?		
	(1)	R.C. Book	(2)	T.C. Book		
	(3)	Driving licence	(4)	None of the above		
143.		permit is provided for seasona	l business.			
	(1)	Goods carriage	(2)	Contract carriage		
	(3)	National	(4)	Temporary		
144.	What is the term used for the person to whom goods are sent and to whom the intended to be delivered?					
	(1)	Consigner	(2)	Consignee		
	(3)	Operator	(4)	None of the above		
145.	Whi	ich data is mainly recorded in the	"log book"	of the vehicle ?		
	(1)	Performance of the vehicle				
	(2)	Running time for a trip				
	(3)	Loading, unloading of vehicle				
	(4)	None of the above				

AYT	•								
146.	Whi	ich are the three colour lights used in traffi	c s	ignal ?					
	(1)	Red, Green and Black							
	(2)	Blue, Green and Red							
	(3)	Blue, Pink and Green							
	(4)	Red, Green and Amber							
147.	Veh	icles exempted from paying motor vehicle	s'	tax are	_				
	(1)								
	(2)	(2) taxis							
	(3)	state transport buses							
	(4)	two wheelers							
148.	Con	Consignment note gives the details regarding							
	(1)	goods to be transported							
	(2)	number of trips made							
	(3)	purchase of the vehicle							
	(4)	4) tax paid							
149.	Which organisation conducts the training programmes to the administrative and superviso staff of MSRTC?								
	(1)	C.I.R.T. (2	2)	TELCO					
	(3)	V.R.D.E.	ł)	A.R.A.I.					
150.	Gros	ss vehicle weight means			_				
	(1)	weight of the load carried by the vehicle	on	ly					
	(2)	2) total weight of the vehicle and load							

weight of the vehicle chassis only

none of the above

(3)